



The Extrudingskill Cleats cross cleats, easily weldable on PVC or PU based belts, to transport products on horizontal, vertical and inclined conveyors. They grant a perfect flexibility and resistance to abrasion and oils.

Material: **PU FDA**  
 Hardness: **SH 85 - 92 A**  
 Colour: **WHITE**  
 Tolerance: **+/- 3 SHA**



| CODE         | TYPE | CARRIERBASE |       | CARRIERHEIGHT |         | CARRIER ANGLE | MIN. PITCH OF CARRIER TRANSV. |      | MIN. DRUM FLEXING TRANSV. |      | (SH A) |
|--------------|------|-------------|-------|---------------|---------|---------------|-------------------------------|------|---------------------------|------|--------|
|              |      | MM          | INCH  | MM            | INCH    |               | MM                            | INCH | MM                        | INCH |        |
| 520503014034 | ES30 | 15          | 19/32 | 30            | 1 3/16  |               |                               |      |                           |      | 85     |
| 520503014037 | ES30 | 15          | 19/32 | 30            | 1 3/16  |               |                               |      |                           |      | 92     |
| 520503014234 | ES40 | 15          | 19/32 | 40            | 1 37/64 |               |                               |      |                           |      | 85     |
| 520503014237 | ES40 | 15          | 19/32 | 40            | 1 37/64 |               |                               |      |                           |      | 92     |
| 520503014334 | ES50 | 15          | 19/32 | 50            | 1 31/32 |               |                               |      |                           |      | 85     |
| 520503014337 | ES50 | 15          | 19/32 | 50            | 1 31/32 |               |                               |      |                           |      | 92     |